



## FWX9650

cod. FWX-9650


**MUSCOLI COINVOLTI**  
**MUSCLE GROUPS**
■ Abductori - Abductors


Bande elastiche non incluse  
Elastic bands not included



SISTEMA DI SPINTA a leveraggi indipendenti divergenti  
 DIMENSIONI PRODOTTO: 1670x765x1456 mm  
 PESO MAX UTILIZZATORE 120 Kg  
 PESO MAX CARICABILE 300 Kg  
 PESO: 112 kg  
 CLASSE D'UTILIZZO PROFESSIONALE (EN20957-1 / EN957-2 classe S)

INDEPENDENT DIVERGENT PUSH leverage system  
 SET UP SIZE: 1670x765x1456 mm  
 MAX USER WEIGHT 120 Kg  
 MAX LOADABLE WEIGHT 300 Kg  
 WEIGHT: 112 kg  
 COMMERCIAL USE (EN20957-1 / EN957-2 class S)

- Struttura tubolare in acciaio a sezione ovale piatta 50x100 mm - spessore 3 mm.
- Verniciatura doppia a polveri epossidiche, antigraffio. Trattamento dei tubolari con sabbiatura e fosfatazione
- Sistema di cuscinetti POWER GRADE per garantire uno scorrimento preciso e progressivo
- Cuscini in schiuma ad alta densità con rivestimento in PU
- Structure oval flat heavy-duty steel tubing 50x100 mm - thickness 3 mm.
- Double heavy duty powder coating painting, scratch-resistant. Tubing treatment with sandblastic and phosphating process
- Pulleys system POWER GRADE bearings for a smooth and precise action
- High-density foam cushions with PU upholstery

